



Baliza led pulso, 12-24vdc, 11 patrones de flash, montaje de imán de vacío, azul

SKU: X7960BVM Marca: ECCO Categoría: Rojo-Azul-Verde

\$4,273.64

Precios con IVA incluido

DESCRIPCIÓN

<div style='width: 100%; max-width: 1200px; margin: 0 auto; font-family: sans-serif; line-height: 1.6; color: inherit; background-color: transparent;*><div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;*><div style='flex: 1 1 300px; min-width: 280px;*><h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;*>Descripción</h3><p style='font-size: 15px; color: inherit;*>7960 Series Pulse® LED beacons offer SAE Class I light output and double or quad flash operation combined with a long maintenance free service life and low amp draw, making this beacon a cost effective choice for many applications. The die-cast aluminum base is coated against corrosion, electronics are encapsulated in epoxy for dust, moisture and vibration protection while the thread-on polycarbonate lens allows easy flash mode selection without tools (via circuit board mounted microswitch). Easily replaces old rotating or strobe beacons with the latest technology so no ongoing maintenance is required. Vacuum-Magnet models feature a 15' straight cigarette cord with switched plug.</p></div></div><div style='display: flex; flex-wrap: wrap; gap: 20px; margin-bottom: 30px;*><div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Especificaciones</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 5px;*>VOLTAGE: 12-24 V<li style='margin-bottom: 5px;*>FLASH PATTERN: 11<li style='margin-bottom: 5px;*>APPROVAL: SAE CLASS I, SAE CLASS II, CAL. TITLE 13, CE, R10<li style='margin-bottom: 5px;*>HEIGHT: 5.7<li style='margin-bottom: 5px;*>WIDTH: 6.5<li style='margin-bottom: 5px;*>WARRANTY: 5 YEAR</div></div><hr style='border: 0; border-top: 1px solid rgba(150, 150, 150, 0.3); margin: 30px 0;*></div>

ESPECIFICACIONES

Característica 1	Salida luminosa SAE Clase I con destello doble o cuádruple para alta visibilidad
Característica 2	Base de aluminio fundido con recubrimiento anticorrosivo para durabilidad extrema
Característica 3	Selección de 11 patrones de flash sin herramientas mediante microinterruptor interno
Característica 4	Electrónica encapsulada en epoxi para protección contra polvo, humedad y vibración
Característica 5	Consumo energético reducido en 12-24 VDC para menor carga eléctrica
Característica 6	Reemplazo directo de balizas rotativas o estroboscópicas sin mantenimiento posterior