

Cámara Domo IP / 2 Megapixel / Dual Light 30 m (98.4 ft) / Micrófono Integrado / IK08 / IP67 / PoE / H.265+

SKU: DS-2CD1123G3-LIUF Marca: HIKVISION Categoría: Domo / Eyeball / Turret

Garantía: 5 años

$1,973.82

Precios con IVA incluido

DESCRIPCIÓN

Cámara domo IP de 2 megapíxeles con tecnología Dual Light que alterna automáticamente entre iluminación IR y luz blanca según la detección de humanos y vehículos mediante AcuSense Lite. Integra micrófono para grabación de audio sincronizada y utiliza compresión H.265+ para optimizar el consumo de ancho de banda y capacidad de almacenamiento. Su lente fija de 2.8 mm proporciona un campo de visión de 103°, mientras que su construcción con certificación IP67 e IK08 la hace apta para instalación en exteriores expuestos a condiciones climáticas adversas y riesgos de impacto. Soporta alimentación PoE para simplificar la instalación y reduce la necesidad de cableado eléctrico adicional.

Desempeño
Resolución: 2 MP (1920 x 1080)
Lente: 2.8 mm fija
Ángulo de visión: 103°
Iluminación: Dual Light (IR + luz blanca) hasta 30 m (98.4 ft)
Detección inteligente: AcuSense Lite (humanos y vehículos)
Compresión: H.265+

Físicas y Eléctricas
Protección: IP67 e IK08 antivandálico
Alimentación: PoE
Audio: Micrófono integrado
Almacenamiento: Ranura Micro SD hasta 512 GB
Uso: Exterior

Contenido del Paquete
Cámara domo IP DS-2CD1123G3-LIUF
Accesorios de montaje
Plantilla de perforación
Manual de instalación

ESPECIFICACIONES

Característica 1	**Iluminación Dual Light con detección de humanos y vehículos**
Característica 2	**Micrófono integrado para audio sincronizado en grabación**
Característica 3	**Compresión H.265+ para reducción de ancho de banda y almacenamiento**
Característica 4	**Domo antivandálico IK08 con protección IP67 para exteriores**
Característica 5	**Ranura Micro SD hasta 512 GB para almacenamiento local**
Característica 6	**Campo de visión de 103° con lente fija de 2.8 mm**

MEMORIA TÉCNICA · DS-2CD1123G3-LIUF

Número de parte de esta ficha: DS-2CD1123G3-LIUF. La información corresponde a esta variante.

DS-2CD1123G3-LIUF
2 MP Smart Hybrid Light 3.0 Fixed Dome Network Camera
- HikAI-ISP for well noise reduction, color correction and image quality improvement
- Motion Detection 3.0 detects persons and vehicles more accurately, reducing false alarms
- Smart Hybrid Light: integrates IR and white lights, 3 supplemental lighting modes
- Built-in microphone for real-time audio security
- -F: Support on-board storage up to 512 GB (SD card slot)
- Dust and water resistant (IP67)
- Specification
Camera
Image Sensor 1/2.9" Progressive Scan CMOS
Max. Resolution 1920 × 1080
Min. Illumination Color: 0.003 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
Shutter Time 1 s to 1/100,000 s
Day & Night IR cut filter
Angle Adjustment Pan: 0° to 355°,tilt: 0° to 75°,rotate: 0° to 355°
Lens
Lens Type Fixed focal lens, 2.8 and 4 mm optional
Focal Length & FOV
2.8 mm, horizontal FOV 104°, vertical FOV 57°, diagonal FOV 121°
4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100°
Lens Mount M12
Focus NA
Iris Type Fixed
Aperture F1.6
Depth of Field
2.8 mm: 1.1 m to ∞
4 mm: 1.2 m to ∞
DORI
DORI
2.8 mm, D: 45 m, O: 18 m, R: 9 m, I: 4 m
4 mm, D: 56 m, O: 22 m, R: 11 m, I: 5 m
Illuminator
Supplement Light Type IR,White Light
Supplement Light Range Up to 30 m
Smart Supplement Light Yes
IR Wavelength 850 nm
Video
Main Stream

50 Hz: 25 fps (1920 × 1080, 1280 × 720)
60 Hz: 30 fps (1920 × 1080, 1280 × 720)
Sub-Stream
50 Hz: 25 fps (640 × 480, 640 × 360)
60 Hz: 24 fps (640 × 480, 640 × 360)
Third Stream NA
Video Compression
- Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate 32 Kbps to 8 Mbps
H.264 Type Baseline Profile,Main Profile,High Profile
H.265 Type Main Profile
Bit Rate Control CBR,VBR
Scalable Video Coding (SVC) YES
Region of Interest (ROI) 1 fixed regions for each stream
Target Cropping NO
Audio
Audio Type Mono sound
Audio Compression -U: G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate
-U: 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps
(MP2L2)/16 to 64 Kbps (AAC-LC)
- Audio Sampling Rate -U 8 kHz/16 kHz
Environment Noise Filtering -U: Yes
Network
Protocols
DHCP,QoS,FTP,SSL/TLS,ICMP,RTSP,UDP,HTTPS,HTTP,DNS,IPv6,IPv4,IGMP,RTCP,RTP,DD
NS,TCP/IP,UPnP,NTP,SMTP
Simultaneous Live View Up to 6 channels
API ISAPI,EZVIZ,ONVIF,ISUP,SDK
User/Host
Up to 32 users
3 user levels: administrator, operator, and user
Security
Password protection, complicated password, watermark, basic and digest
authentication for HTTP, WSSE and digest authentication for Open Network Video
Interface, security audit log, host authentication (MAC address)
Network Storage NO
Client iVMS-4200,Hik-Connect
Web Browser Plug-in required live view: Chrome 91+, Firefox 88+, Edge 91+
Image
Image Parameters Switch Yes
Image Settings
Rotate mode,saturation,brightness,contrast,sharpness,gain,white
balance,AGC,adjustable by client software or web browser
Day/Night Switch Day,Night,Auto,Schedule
Wide Dynamic Range (WDR) Digital WDR
SNR ≥ 52 dB
Image Enhancement BLC,HLC,3D DNR
Privacy Mask 4 programmable polygon privacy masks
Interface
Ethernet Interface 1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Microphone Yes,1 built-in microphone
Built-in Speaker -LIU(F) NA
Audio NA
Alarm NA
Reset Key
- Yes
Event
Basic Event
Video tampering alarm, motion detection (support alarm triggering by specified target
types (human, vehicle)), exception
Smart Event NO
Linkage
Upload to FTP/memory card, notify surveillance center, send email, trigger recording,
trigger capture
Deep Learning Function
Perimeter Protection NO
Face Capture NO
- General
Power
12 VDC ± 25%, 0.5 A, max. 6 W,Ø 5.5 mm coaxial power plug,reverse polarity
protection,
PoE: IEEE 802.3af, Class 3, max. 7.5 W
Material Base: metal, cover: plastic
Dimension Ø 121.5 mm × 97.6 mm (Ø 4.78" × 3.84")
Package Dimension 150 mm × 150 mm × 141 mm (5.91" × 5.91" × 5.55")
Weight Approx. 480 g (1.06 lb.)
With Package Weight -LIU(F): Approx. 635 g (1.40 lb.)
Storage Conditions -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating
Conditions
-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language
English, Russian, Ukrainian, Arabic, Spanish, French, Portuguese, Turkish, Polish,
German
General Function Heartbeat,mirror,password reset via email,password protection,anti-banding
Flashing Light NA
Approval
EMC
CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC
61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021
Safety
CB: IEC 62368-1: 2014+A11,
CE-LVD: EN 62368-1: 2014/A11: 2017
Environment
CE-RoHS: 2011/65/EU,
WEEE: 2012/19/EU,
Reach: Regulation (EC) No 1907/2006
Protection IP67: IEC 60529-2013
- Dimension
- Accessory
- Optional
- DS-1276ZJ-SUS DS-1272ZJ-120 DS-1275ZJ-SUS DS-220AZJ-130-WA DS-1275ZJ-S-SUS
- DS-1272ZJ-120B DS-4221ZJ-WC DS-220AZJ-145-WA DS-1271ZJ-120 DS-1476ZJ-SUS
- DS-1475ZJ-SUS DS-1280ZJ-DM46
- Installation Methods
Corner Mounting

DS-1276ZJ-SUS+DS-12
72ZJ-120
Corner Mounting
DS-1476ZJ-SUS+DS-22
0AZJ-130-WA
Wall Mounting
DS-1272ZJ-120
Wall Mounting
DS-220AZJ-130-WA
Wall Mounting
DS-1272ZJ-120B+DS-1
253ZJ-M
- Wall Mounting
DS-220AZJ-145-WA
Vertical Pole
Mounting
DS-1275ZJ-SUS+DS-12
72ZJ-120B
Vertical Pole
Mounting
DS-1275ZJ-S-SUS+DS-
220AZJ-130-WA
Vertical Pole
Mounting
DS-1475ZJ-SUS+DS-22
0AZJ-145-WA
In-Ceiling Mounting
DS-4221ZJ-WC
- Pendant Mounting
DS-1271ZJ-120+DS-12
80ZJ-DM46
Junction Box
DS-1280ZJ-DM46