

Cámara Turret IP / 2 Megapixel / Dual Light 30 m (98.4 ft) / AcuSense Lite / Micrófono Integrado / IP67 / PoE

SKU: DS-2CD1323G3-LIU Marca: HIKVISION Categoría: Domo / Eyeball / Turret

Garantía: 5 años

$1,602.61

Precios con IVA incluido

DESCRIPCIÓN

Cámara de red tipo turret de 2 megapíxeles diseñada para videovigilancia profesional en exteriores. Integra tecnología AcuSense Lite para la detección precisa de humanos y vehículos, reduciendo falsas alarmas causadas por movimientos irrelevantes. Equipada con iluminación dual IR y luz blanca de alcance de 30 m (98.4 ft), permite operación en modo nocturno a color cuando se activa la iluminación visible. Incorpora micrófono integrado para audio ambiental, compresión H.265+/H.265 para optimización de almacenamiento y transmisión, y protección IP67 para resistencia a condiciones climáticas adversas. La alimentación PoE 802.3af simplifica la instalación mediante un solo cable de red.

Características Generales
Resolución máxima: 2 Megapixel (1920 x 1080)
Sensor: 1/2.7' progresivo scan CMOS
Distancia focal: 2.8 mm con ángulo de visión de 103°
Iluminación mínima color: 0.005 lux @ (F1.6, AGC ON)
Iluminación mínima B/N: 0 lux con IR
Día/noche real con filtro ICR
Iluminación IR EXIR: 30 m (98.4 ft)
Iluminación luz blanca: 30 m (98.4 ft)
Micrófono integrado
WDR digital, 3D DNR, BLC
Compresión: H.265+, H.265, H.264+, H.264
Detección inteligente: humanos y vehículos (AcuSense Lite)
Compatible con Hik-Connect
Protección: IP67
Alimentación: PoE 802.3af
Compatible ONVIF

Desempeño de Imagen
Resolución: 1920 x 1080
Lente: 2.8 mm, 103° HFOV
Mínima iluminación color: 0.005 lux
Mínima iluminación B/N: 0 lux (IR)
Día/noche: Real con filtro ICR
WDR digital, 3D DNR, BLC

Iluminación y Audio
IR EXIR: 30 m (98.4 ft)
Luz blanca: 30 m (98.4 ft)
Micrófono integrado
Entradas de audio: N/A
Salidas de audio: N/A
Entradas de alarma: N/A
Salidas de alarma: N/A

Red y Físicas
Compresión: H.265+, H.265, H.264+, H.264
Compatible ONVIF
Compatible Hik-Connect
Alimentación: PoE 802.3af
Protección: IP67
Tipo: Turret para exterior

ESPECIFICACIONES

Característica 1	**Detección inteligente de humanos y vehículos con AcuSense Lite**
Característica 2	**Micrófono integrado para captura de audio ambiental en tiempo real**
Característica 3	**Doble iluminación IR y luz blanca para visión nocturna a color hasta 30 m (98.4 ft)**
Característica 4	**Compresión H.265+ para reducir ancho de banda y requerimientos de almacenamiento**
Característica 5	**WDR digital y 3D DNR para imagen clara en condiciones de luz contrastante**
Característica 6	**Compatible con Hik-Connect para monitoreo remoto centralizado**

MEMORIA TÉCNICA · DS-2CD1323G3-LIU

Número de parte de esta ficha: DS-2CD1323G3-LIU. La información corresponde a esta variante.

DS-2CD1323G3-LIU
2 MP Smart Hybrid Light 3.0 Fixed Turret Network Camera
- HikAI-ISP for well noise reduction, color correction and image quality improvement
- Motion Detection 3.0 detects persons and vehicles more accurately, reducing false alarms
- Smart Hybrid Light: integrates IR and white lights, 3 supplemental lighting modes
- Built-in microphone for real-time audio security
- Dust and water resistant (IP67)
- Specification
Camera
Image Sensor 1/2.9" Progressive Scan CMOS

Max. Resolution 1920 × 1080
Min. Illumination Color: 0.003 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
Shutter Time 1 s to 1/100,000 s
Day & Night IR cut filter
Angle Adjustment Pan: 0° to 360°,tilt: 0° to 75°,rotate: 0° to 360°
Lens
Lens Type Fixed focal lens, 2.8 and 4 mm optional
Focal Length & FOV
2.8 mm, horizontal FOV 104°, vertical FOV 57°, diagonal FOV 121°
4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100°
Lens Mount M12
Focus NA
Iris Type Fixed
Aperture F1.6
Depth of Field
2.8 mm: 1.1 m to ∞
4 mm: 1.2 m to ∞
DORI
DORI
2.8 mm, D: 45 m, O: 18 m, R: 9 m, I: 4 m
4 mm, D: 56 m, O: 22 m, R: 11 m, I: 5 m
Illuminator
Supplement Light Type IR,White Light
Supplement Light Range Up to 30 m
Smart Supplement Light Yes
IR Wavelength 850 nm
Video
Main Stream
50 Hz: 25 fps (1920 × 1080, 1280 × 720)
60 Hz: 30 fps (1920 × 1080, 1280 × 720)
Sub-Stream
50 Hz: 25 fps (640 × 480, 640 × 360)
60 Hz: 24 fps (640 × 480, 640 × 360)
Third Stream NA
Video Compression
- Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate 32 Kbps to 8 Mbps
H.264 Type Baseline Profile,Main Profile,High Profile
H.265 Type Main Profile
Bit Rate Control CBR,VBR
Scalable Video Coding (SVC) YES
Region of Interest (ROI) 1 fixed regions for each stream
Target Cropping NO
Audio
Audio Type Mono sound
Audio Compression -U: G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate
-U: 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps
(MP2L2)/16 to 64 Kbps (AAC-LC)
- Audio Sampling Rate -U: 8 kHz/16 kHz
Environment Noise Filtering -U: Yes
Network
Network
Protocols
DHCP,QoS,FTP,SSL/TLS,ICMP,RTSP,UDP,HTTPS,HTTP,DNS,IPv6,IPv4,IGMP,RTCP,RTP,DD
NS,TCP/IP,UPnP,NTP,SMTP
Simultaneous Live View Up to 6 channels
API ISAPI,EZVIZ,ONVIF,ISUP,SDK
User/Host
Up to 32 users
3 user levels: administrator, operator, and user
Security
Password protection, complicated password, watermark, basic and digest
authentication for HTTP, WSSE and digest authentication for Open Network Video
Interface, security audit log, host authentication (MAC address)
Network Storage NO
Client iVMS-4200,Hik-Connect
Web Browser Plug-in required live view: Chrome 91+, Firefox 88+, Edge 91+
Image
Image Parameters Switch Yes
Image Settings
Rotate mode,saturation,brightness,contrast,sharpness,gain,white
balance,AGC,adjustable by client software or web browser
Day/Night Switch Day,Night,Auto,Schedule
Wide Dynamic Range (WDR) Digital WDR
SNR ≥ 52 dB
Image Enhancement BLC,HLC,3D DNR
Privacy Mask 4 programmable polygon privacy masks
Interface
Ethernet Interface 1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage NA
Built-in Microphone Yes,1 built-in microphone
Built-in Speaker -LIU(F)□ NA
Audio NA
Alarm NA
Reset Key NA
Event
Basic Event
Video tampering alarm, motion detection (support alarm triggering by specified target
types (human, vehicle)),exception
Smart Event NO
Linkage
Upload to FTP/memory card, notify surveillance center, send email, trigger recording,
trigger capture
Deep Learning Function
Perimeter Protection NO
Face Capture NO
General
Power
12 VDC ± 25%, 0.5 A, max. 6.0 W,Ø 5.5 mm coaxial power plug,
PoE: IEEE 802.3af, Class 3, max. 7.0 W
Material Cover: PLASTIC, main body: Metal
Dimension Ø 110 mm × 93 mm (Ø 4.33" × 3.66")
- Package Dimension 134 mm × 134 mm × 108 mm (5.28" × 5.28" × 4.25")
Weight Approx. 375 g (0.83 lb.)
With Package Weight -LIU(F): Approx. 515 g (1.14 lb.)
Storage Conditions -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating
Conditions

-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language
English, Russian, Ukrainian, Arabic, Spanish, French, Portuguese, Turkish, Polish,
German
General Function Heartbeat,mirror,password reset via email,password protection,anti-banding
Flashing Light NA
Approval
EMC
CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC
61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021
Safety
CB: IEC 62368-1: 2014+A11,
CE-LVD: EN 62368-1: 2014/A11: 2017
Environment
CE-RoHS: 2011/65/EU,
WEEE: 2012/19/EU,
Reach: Regulation (EC) No 1907/2006
Protection IP67: IEC 60529-2013
- Dimension
- Accessory
- Optional
DS-1275ZJ-SUS DS-1271ZJ-110-TRS DS-1280ZJ-S DS-1281ZJ-S DS-1275ZJ-S-SUS
- DS-1272ZJ-110-TRS DS-1280ZJ-TR13 DS-1475ZJ-SUS DS-1276ZJ-SUS DS-220AZJ-145-WA
- DS-220AZJ-130-WA DS-1476ZJ-SUS
- Installation Methods
Vertical Pole
Mounting
DS-1275ZJ-SUS+DS-12
81ZJ-S
Vertical Pole
Mounting
DS-1275ZJ-S-SUS+DS-
220AZJ-130-WA
Vertical Pole
Mounting
DS-1475ZJ-SUS+DS-22
0AZJ-145-WA
Pendant Mounting
DS-1271ZJ-110-TRS
Junction Box
DS-1280ZJ-S
- Junction Box
DS-1280ZJ-TR13
Inclined Ceiling
Mounting
DS-1281ZJ-S
Wall Mounting
DS-1272ZJ-110-TRS+D
S-1253ZJ-M
Wall Mounting
DS-220AZJ-145-WA
Wall Mounting
DS-220AZJ-130-WA
- Corner Mounting
DS-1276ZJ-SUS+DS-12
72ZJ-110-TRS
Corner Mounting
DS-1476ZJ-SUS+DS-22
0AZJ-130-WA