

Cámara Turret IP / 6 Megapixel / Panorámica 180° / Dual Light 30 m (98.4 ft) / PoE / Audio Bidireccional / IP67

SKU: IPC-T260HAD-LUF/SL Marca: HiLook by HIKVISION Categoría: Fisheye y Hemisféricas

Garantía: 3 años

$4,440.50

Precios con IVA incluido

DESCRIPCIÓN

Cámara de red tipo turret con resolución de 6 megapíxeles (3632 × 1632) diseñada para aplicaciones de videovigilancia profesional en exteriores. Integra lente fijo de 2.8 mm con ángulo de visión panorámico de 180°, permitiendo monitorear áreas extensas con una única unidad. El sistema de iluminación Dual Light combina Smart IR y luz blanca con alcance de 30 m (98.4 ft), adaptándose automáticamente a las condiciones de iluminación del entorno. Incorpora micrófono y bocina integrados para comunicación bidireccional, facilitando la intervención remota en tiempo real. La compresión H.265+ optimiza el uso de ancho de banda y capacidad de almacenamiento, mientras que la protección IP67 garantiza operación continua en condiciones climáticas adversas.

Características Generales
• Resolución máxima: 6 MP (3632 × 1632)
• Lente fijo: 2.8 mm, ángulo de visión horizontal 180°
• Iluminación Dual Light: Smart IR 30 m (98.4 ft) + luz blanca 30 m (98.4 ft)
• Audio bidireccional con micrófono y altavoz integrados
• Compresión de video: H.265+, H.265, H.264+, H.264
• Procesamiento de imagen: 3D DNR, BLC, HLC, DWDR
• Detección de movimiento con filtro de humanos
• Notificaciones push mediante aplicación HiLook Vision
• Alarma visual y auditiva integrada
• Soporte Micro SD hasta 512 GB (no incluida)
• Montaje en pared o techo

Desempeño
Resolución: 6 MP (3632 × 1632)
Lente: 2.8 mm fijo
Ángulo de visión: 180°
Smart IR: 30 m (98.4 ft)
Luz blanca: 30 m (98.4 ft)
Procesamiento: 3D DNR, BLC, HLC, DWDR
Detección: Movimiento con filtro humano
Notificaciones: Push en app
Compresión: H.265+, H.265, H.264+, H.264

Físicas / Eléctricas
Alimentación: 12 VDC / 10 W
PoE: 802.3af, 11.5 W
Protección: IP67
Material: Policarbonato reforzado
Montaje: Pared o techo
Aplicación: Interior / Exterior

Contenido del Paquete
• Cámara Turret IP
• Kit de montaje
• Guía de instalación
• Tarjeta de garantía

ESPECIFICACIONES

Característica 1	**Visión panorámica 180° con lente fijo 2.8 mm para cobertura total de área amplia**
Característica 2	**Audio bidireccional con micrófono y bocina integrados para intervención remota**
Característica 3	**Smart IR + luz blanca inteligente con alcance de 30 m (98.4 ft) en condiciones de oscuridad**
Característica 4	**Compresión H.265+ que reduce hasta un 50% el consumo de ancho de banda y almacenamiento**
Característica 5	**Detección de movimiento con filtrado de humanos para alertas precisas sin falsos positivos**
Característica 6	**Almacenamiento local Micro SD hasta 512 GB como respaldo ante fallas de red**

MEMORIA TÉCNICA · IPC-T260HAD-LUF/SL

Número de parte de esta ficha: IPC-T260HAD-LUF/SL. La información corresponde a esta variante.

IPC-T260HAD-LUF/S(L)(RB)
6 MP Smart Hybrid Light Fixed Turret Network Camera
- High quality imaging with 6 MP resolution
- Support Person and Vehicle Detection
- Smart Hybrid Light: advanced technology with long range
- Efficient H.265+ compression technology
- Support on-board storage up to 512 GB (SD card slot)
- Provide real-time security via built-in two-way audio
- Water and dust resistant (IP67)
- 180° Field of view
- Active strobe light and audio alarm to warn intruders off
- Specification
Camera
Image Sensor 1/2.5" Progressive Scan CMOS
Max. Resolution 3632 × 1632
Min. Illumination Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with light

Shutter Time 1 s to 1/100,000 s
Day & Night IR cut filter
Angle Adjustment Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°
Lens
Lens Type Fixed focal lens, 2.8 mm
Focal Length & FOV 2.8 mm, horizontal FOV 180°, vertical FOV 77°
Lens Mount M12
Iris Type Fixed
Aperture F1.6
DORI
DORI 2.8 mm, D: 42 m, O: 16 m, R: 8 m, I: 4 m
Illuminator
Supplement Light Type IR, White Light
Supplement Light Range Up to 30 m
Smart Supplement Light Yes
IR Wavelength 850 nm
Video
Main Stream
50 Hz: 20 fps (3632 × 1632)
60 Hz: 20 fps (3632 × 1632)
Sub-Stream
50 Hz: 20 fps (1200× 536, 960 × 432)
60 Hz: 20 fps (1200× 536, 960 × 432)
Video Compression
Main stream: H.265+/H.265/H.264+/H.264,
Sub-stream: H.265/H.264/MJPEG
Video Bit Rate 32 Kbps to 16 Mbps
H.264 Type Baseline Profile, Main Profile, High Profile
H.265 Type Main Profile
Bit Rate Control CBR, VBR
Region of Interest (ROI) 1 fixed region for main stream
Scalable Video Coding (SVC) H.264 and H.265 encoding
Audio
Audio Type Mono sound
Audio Sampling Rate 8 kHz/16 kHz
Environment Noise Filtering Yes
Audio Compression G.711/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio Bit Rate
64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps
(MP2L2)/16 to 64 Kbps (AAC-LC)
Network
Security
Password protection, complicated password, watermark, basic and digest
authentication for HTTP, WSSE and digest authentication for Open Network Video
Interface, security audit log, host authentication (MAC address)
Simultaneous Live View Up to 6 channels
- API ONVIF (Profile S, Profile T, Profile G), ISAPI, SDK
Protocols
TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IPv4, IPv6, IGMP, UDP, QoS,
FTP, SMTP
User/Host
Up to 32 users
3 user levels: administrator, operator, and user
Client iVMS-4200, HiLookVision
Web Browser
Plug-in required live view: IE 11,
Local service: Chrome 80+, Firefox 80+, Edge 89+
Image
Wide Dynamic Range (WDR) 120 dB
SNR ≥ 52 dB
Day/Night Switch Day, Night, Auto, Schedule
Image Enhancement BLC, HLC, 3D DNR
Image Settings
Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance,
adjustable by client software or web browser
Privacy Mask 4 programmable polygon privacy masks
Interface
Ethernet Interface 1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Microphone Yes, 1 built-in microphone
Built-in Speaker
Yes, 1 built-in speaker, Max. power consumption: 2 W, max. sound pressure level: 10
cm: 97 dB.
Reset Key Yes
Event
Basic Event
Motion detection (support alarm triggering by specified target types (human and
vehicle)), video tampering alarm, exception
Linkage
Upload to FTP, upload to memory card, send email, notify surveillance center, trigger
recording, trigger capture, audible warning, strobe light flashing
General
Power
12 VDC ± 25%, 0.83 A, max. 10 W, Ø 5.5 mm coaxial power plug, reverse polarity
protection,
PoE: IEEE 802.3af, Class 3, max. 11.5 W
Material Base: Metal , cover: Plastic
Dimension Ø 130.1 mm × 109.1 mm (Ø 5.1" × 4.3")
Package Dimension 150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.6")
Weight Approx. 580 g (1.3 lb.)
With Package Weight Approx. 760 g (1.7 lb.)
Storage Conditions -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating
Conditions
-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language
English, Turkish, Polish, Romanian, Czech, Slovak, Traditional Chinese, Thai,
Vietnamese, Croatian, Slovenian, Serbian, Ukrainian
General Function Heartbeat, anti-banding, password protection, password reset via email
Flashing Light
/SRB model: Red and Blue Light
/SL model: White Light
- Approval
EMC
CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC
61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021,
IC: ICES-003: Issue 7,
KC: KN32: 2015, KN35: 2015

Safety CB: IEC 62368-1: 2014+A11
Environment
CE-RoHS: 2011/65/EU,
WEEE: 2012/19/EU,
Reach: Regulation (EC) No 1907/2006
Protection IP67: IEC 60529-2013
- Typical Application
Recommended Scenarios: The Dual-lens panoramic camera is ideal for large-scale application Scenarios, such as parks, parking lots, intersections, roads, stadiums, and plantations.
- Recommended installation height of the camera: above 3 m (9.84 ft.).
- Recommended physical distance between the object and camera lens: 8 to 12 m (26.24 ft. to 39.37 ft.).
- Recommended vertical angle of the camera lens: 68° to 75°.
- Dimension
- Available Model
IPC-T260HAD-LUF/SL(2.8mm)
IPC-T260HAD-LUF/SRB(2.8mm)
- Accessory
- Optional
DS-1273ZJ-130-TRL
Wall mount
DS-1280ZJ-DM21
Junction box
DS-1281ZJ-M
Inclined ceiling mount