

WiFi and Broadband RF Coax Connectors Product

RMC-6010-B



- MC Card
- Connector: RF
- Gender: Plug
- Body Style: Right Angle
- Attachment Style: Crimp
- **Cable**
- RG-316/U
- Cable Group [B](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RMC-6010-B1



- MC Card
- Connector: RF
- Gender: Plug
- Body Style: Right Angle
- Attachment Style: Crimp
- **Cable**
- Cable Group [B1](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-700-179-1



- SSMB 75 Ohm
- Connector: RF
- Gender: Plug (Male Pin)
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity
- **Cable**
- RG-179/U
- Cable Group [S](#)
- **Plating**
- Body Plating: Gold
- Contact Plating: Gold
- Dielectric: PTFE

RP-1005-C



- N 50 Ohm
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-58/U
- Cable Group [C](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1006-3I



- N 50 Ohm
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-8/U, Times LMR®-400 and Belden 9913
- Cable Group [I](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1028-I



- N 50 Ohm
- Connector: RF
- Gender: Female Jack
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-8/U, Times LMR®-400 and Belden 9913
- Cable Group [I](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1106-C



- BNC 50 Ohm
- Connector: RF
- Gender: Male
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-58/U
- Cable Group [C](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1106-C1



- BNC
- Connector: RF
- Gender: Male
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-142/U
- Cable Group [C1](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1106-C2



- BNC 50 Ohm
- Connector: RF
- Gender: Male
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- Times LMR®-200
- Cable Group [C2](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1116-NG



- BNC
- Connector: RF
- Gender: Female
- Body Style: Front Mount Bulkhead
- Attachment Style: Solder
- D-Flat
- Reverse Polarity (Gender)
- **Cable**
- Times LMR®-200
- Cable Group [C2](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1117-BT



- BNC 50 Ohm
- Connector: RF
- Gender: Female Jack
- Body Style: Bulkhead
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-174/U and RG-316/U
- Cable Group [B](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1117-C



- BNC 50 Ohm
- Connector: RF
- Gender: Female Jack
- Body Style: Rear Mount Bulkhead
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**

- RG-58/U
- Cable Group [C](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1117-C1



- BNC 50 Ohm
- Connector: RF
- Gender: Female Jack
- Body Style: Rear Mount Bulkhead
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-142/U
- Cable Group [C1](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-1B



- TNC 50 Ohm
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-174/U and RG-316/U
- Cable Group [B](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-1B1



- TNC 50 Ohm

- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-316/U Double Shield
- Cable Group [B1](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-C



- TNC 50 Ohm
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-58/U
- Cable Group [C](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-C1



- TNC
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-174/U and RG-316/U
- Cable Group [C1](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-C2



-
- TNC
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- Times LMR®-200
- Cable Group [C2](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-C3



-
- TNC
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- Plenum RG-58/U
- Cable Group [C3](#), [M](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

RP-1202-I



-
- TNC 50 Ohm
- Connector: RF
- Gender: Male Plug
- Body Style: Straight
- Attachment Style: Crimp
- Reverse Polarity (Gender)
- **Cable**
- RG-8/U Type, Times LMR®-400 and Belden 9913
- Cable Group [I](#)
- **Plating**
- Body Plating: Nickel
- Contact Plating: Gold
- Dielectric: PTFE

EPCOM syscom – 1630 Paisano Dr. – El Paso. Tx 79901.

Ph (915)533-5119

www.epcom.net