



CPE de Exterior de 5 GHz a 300Mbps, Antena direccional de 23dBi, potencia de 27 dBm, PoE pasivo

SKU: CPE610 Marca: TP-LINK Categoría: 5 y 6 GHz

\$1,569.27

Precios con IVA incluido

DESCRIPCIÓN

<div style='width: 100%; max-width: 1200px; margin: 0 auto; font-family: sans-serif; line-height: 1.6; color: inherit; background-color: transparent;'> <!-- Sección de características de hardware --> <div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;'> <div style='flex: 1 1 300px; min-width: 280px;'> <h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;'>CARACTERÍSTICAS DE HARDWARE</h3> <ul style='padding-left: 20px; font-size: 15px; color: inherit;'> <li style='margin-bottom: 5px;'>Procesador: Qualcomm 560MHz CPU, MIPS 74Kc <li style='margin-bottom: 5px;'>Memoria: 64MB DDR2 RAM, 8MB Flash <li style='margin-bottom: 5px;'>Interface: 1 10/100Mbps Shielded Ethernet Port (LAN/POE)
1 Reset Button <li style='margin-bottom: 5px;'>Fuente de Alimentación: Passive Power over Ethernet via LAN (+4,5pins; -7,8pins)
Voltage range: 16-27VDC <li style='margin-bottom: 5px;'>Dimensiones (W X D X H): 366 x 280 x 207 mm (14.4 x 11.0 x 8.1 in.) <li style='margin-bottom: 5px;'>Dimensiones: 360 x 280 x 207 mm (14.4 x 11.0 x 8.1 in.) (No mount) <li style='margin-bottom: 5px;'>Ganancia de Antena: 23dBi <li style='margin-bottom: 5px;'>Cobertura de Antena: 9° (Azimuth), 7° (Elevation) <li style='margin-bottom: 5px;'>Protección: 15KV ESD Protection
6KV Lightning Protection <li style='margin-bottom: 5px;'>Cercado: Material: Outdoor PC stabilized plastic
Weatherproof: IP65 water and dust proof design </div> <!-- Sección de características inalámbricas --> <div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;'> <div style='flex: 1 1 300px; min-width: 280px;'> <h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;'>CARACTERÍSTICAS INALÁMBRICAS</h3> <ul style='padding-left: 20px; font-size: 15px; color: inherit;'> <li style='margin-bottom: 5px;'>Estándares Inalámbricos: IEEE 802.11a/n <li style='margin-bottom: 5px;'>Protocolo Propietario: TDMA Mode (with Pharos MAXstream enabled) <li style='margin-bottom: 5px;'>Velocidades Inalámbricas: Up to 300Mbps (40MHz, Dynamic)
Up to 144.4Mbps (20MHz, Dynamic)
Up to 72.2Mbps (10MHz, Dynamic)
Up to 36.1Mbps (5MHz, Dynamic) <li style='margin-bottom: 5px;'>Frecuencia: 5.15~5.85GHz <li style='margin-bottom: 5px;'>Potencia de Transmisión: Max. 27dBm (Adjustable power by 1dBm) </div> <!-- Sección de características de software --> <div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;'> <div style='flex: 1 1 300px; min-width: 280px;'> <h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;'>CARACTERÍSTICAS DE SOFTWARE</h3> <ul style='padding-left: 20px; font-size: 15px; color: inherit;'> <li style='margin-bottom: 5px;'>Configuración De Red: WAN: Static/Dynamic/PPPoE/L2TP/PPTP
LAN: Static/Dynamic/DHCP
Forwarding: ALG/UPnP/Virtual Server/Port Trigger
Security: SPI Firewall/ Ping Forbidden/DoS Protection
Access Control
Static Routing
Bandwidth Control
IP & MAC Binding <li style='margin-bottom: 5px;'>Configuraciones Inalámbricas: Pharos MAXstream TDMA Technology
Selectable Channel Width: 5/10/20/40MHz
Auto Channel Selection
Transmit Power Control
Dynamic Frequency Selection(DFS)
WDS Enable/Disable
Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption,
64/128/152-bit WEP Encryption
SSID Broadcast Enable/Disable
Multi-SSID with VLAN Tagging(AP Mode only)
Distance/ACK Timeout Setting
Wireless MAC Address Filter
Wireless Advanced:
Beacon Interval/RTS Threshold/Fragmentation Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia <li style='margin-bottom: 5px;'>Administración: Discovery and Remote Management via Pharos Control application
HTTP/HTTPS Web-based management
System log
SNMP Agent(v2c)
Ping Watch Dog
Dynamic DDNS
SSH Server <li style='margin-bottom: 5px;'>Herramientas de sistema: Indicators: Signal Strength/Noise/Transmit CCO/CPU/Memory
Monitors: Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP
Spectrum Analyzer
Speed Test
Ping
Traceroute <li style='margin-bottom: 5px;'>Optimizaciones a Nivel de Sistema: Optimized IGMP Snooping/Proxy for multicast applications
Hardware watch dog </div> <!-- Sección de características del adaptador PoE --> <div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;'> <div style='flex: 1 1 300px; min-width: 280px;'> <h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;'>OTROS</h3> <ul style='padding-left: 20px; font-size: 15px; color: inherit;'> <li style='margin-bottom: 5px;'>Certificaciones: CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark <li style='margin-bottom: 5px;'>Dimensiones(W x D x H): 85.8x43.9x29.7 mm <li style='margin-bottom: 5px;'>Interfaces: 1 AC Jack with Earth Ground
1 10/100Mbps Shielded Ethernet Port (Power + Data)
1 10/100Mbps Shielded Ethernet Port (Data) <li style='margin-bottom: 5px;'>Botón: Remote Reset Button <li style='margin-bottom: 5px;'>Power Status LEDs: Green <li style='margin-bottom: 5px;'>Input: 100-240VAC, 50/60Hz <li style='margin-bottom: 5px;'>Output: 24VDC, 0.5A Max
+4, 5pins; -7, 8pins. (Support up to 60m Power over Ethernet) <li style='margin-bottom: 5px;'>Eficiencia: >84.29% <li style='margin-bottom: 5px;'>Certificaciones: CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark <li style='margin-bottom: 5px;'>Contenidos del Paquete: Outdoor Wireless CPE
24V 0.5A Passive PoE Adapter
Pole Mounting Straps
AC Power Cord
Installation Guide <li style='margin-bottom: 5px;'>Requisitos del Sistema: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux.
Note: We recommend you to use one of following Web browsers for an improved user experience: Google Chrome, Safari, and Firefox. IE browsers are not recommended. <li style='margin-bottom: 5px;'>Ambiente: Operating Temperature: -40°C~70°C (-40°F~158°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~95% non-condensing </div> </div> <div style='border: 0; border-top: 1px solid rgba(150, 150, 150, 0.3); margin: 30px 0;'> </div>

ESPECIFICACIONES

Característica 1	CPU Qualcomm 560 MHz para procesamiento eficiente de tráfico
Característica 2	Memoria DDR2 de 64 MB para rendimiento estable
Característica 3	Protección ESD 15 kV y contra rayos 6 kV
Característica 4	Diseño IP65 resistente a agua y polvo
Característica 5	Potencia ajustable en incrementos de 1 dBm
Característica 6	Cobertura direccional precisa 9° azimuth / 7° elevation