



e-Lighten ONU / Punto de Acceso Híbrido Para solución de Fibra, Uplink Gigabit para Fibra SC/UPC, 3 puertos LAN Gigabit, 1 Puerto Análogo Telefonía

SKU: RG-APF1250 Marca: RUIJIE Categoría: Puntos de Acceso

\$1,771.89

Precios con IVA incluido

DESCRIPCIÓN

<div style='width: 100%; max-width: 1200px; margin: 0 auto; font-family: sans-serif; line-height: 1.6; color: inherit; background-color: transparent;*><div style='margin-bottom: 30px;*><h2 style='font-size: 24px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;*>Key Specification</h2></div><!-- Sección de especificaciones --><div style='display: flex; flex-wrap: wrap; gap: 20px; margin-bottom: 30px;*><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Performance</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Max. Data Rate: 300 Mbps at 2.4 GHz, 867 Mbps at 5GHz</div></div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Physical</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Dimensions (W x D x H): 165 mm x 86 mm x 29 mm (6.50 in. x 3.39 in. x 1.14 in.) (mounting brackets excluded)<li style='margin-bottom: 8px;*>Net Weight: 0.236 kg (0.52 lbs.)</div></div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Ports</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Service Ports:<ul style='padding-left: 30px; margin: 0; font-size: 14px; list-style-type: circle;*><li style='margin-bottom: 4px;*>1 x 1G SC port<li style='margin-bottom: 4px;*>3 x 10/100/1000BASE-T Ethernet ports<li style='margin-bottom: 4px;*>1 x phone port</div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Power</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Local Power: Support, 1 x DC power connector (12 V/1.5 A)</div></div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Environmental</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Operating Temperature: 0°C to 40°C (32°F to 104°F)<li style='margin-bottom: 8px;*>Bi-directional Optical Sub-Assembly (BOSA) Receiver Sensitivity: -8 dB to -28 dB</div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Certifications</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Certification: CE, CB, SDPPI, MIC, NBTC, SIRIM</div><div style='flex: 1 1 400px; min-width: 280px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden;*><div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 16px; color: inherit; background-color: rgba(0,0,0,0.05);*>Warranty</div><div style='padding: 15px; color: inherit;*><ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*><li style='margin-bottom: 8px;*>Warranty: 3 years</div></div><!-- Imágenes --><div style='display: grid; grid-template-columns: repeat(auto-fill, minmax(280px, 1fr)); gap: 20px; margin-bottom: 30px;*><div style='border: 1px solid rgba(150,150,150,0.3); border-radius: 8px; overflow: hidden;*>src='https://ftp3..mx/usuarios/fotos/RGAPF1250/223716-2024-12-27_17_58_45-rg-apf1250_ac1200_e-lighten_multi-service_wall-mount_ap_-ruijie_reyee.png' alt='' class='fr-fic fr-dii'</div><div style='border: 1px solid rgba(150,150,150,0.3); border-radius: 8px; overflow: hidden;*>src='https://ftp3..mx/usuarios/fotos/RGAPF1250/223716-2024-12-27_17_59_08-rg-apf1250_ac1200_e-lighten_multi-service_wall-mount_ap_-ruijie_reyee.png' alt='' class='fr-fic fr-dii'</div><div style='border: 1px solid rgba(150,150,150,0.3); border-radius: 8px; overflow: hidden;*>src='https://ftp3..mx/usuarios/fotos/RGAPF1250/223716-2024-12-27_17_59_23-.png' alt='' class='fr-fic fr-dii'</div><div style='border: 1px solid rgba(150,150,150,0.3); border-radius: 8px; overflow: hidden;*>src='https://ftp3..mx/usuarios/fotos/RGAPF1250/223716-2024-12-27_17_59_37-rg-apf1250_ac1200_e-lighten_multi-service_wall-mount_ap_-ruijie_reyee.png' alt='' class='fr-fic fr-dii'</div></div><!-- Separador --><hr style='border: 0; border-top: 1px solid rgba(150, 150, 150, 0.3); margin: 30px 0;*></div>

ESPECIFICACIONES

Característica 1	Wi-Fi dual band 300 Mbps + 867 Mbps para alta densidad de usuarios
Característica 2	Integración ONU y AP en un solo equipo para despliegues FTTH simplificados
Característica 3	Telefonía analógica POTS para servicios triple play residencial y SOHO
Característica 4	BOSA óptica con sensibilidad -28 dB para enlaces de fibra de largo alcance
Característica 5	Alimentación local DC 12V/1.5A para instalaciones sin infraestructura PoE
Característica 6	Chasis compacto de 165 x 86 x 29 mm para ubicaciones con espacio limitado

Documento generado por RimeCommerce · SOITMEX | 04/08/2026 12:02