

Estación de Alarma de Pánico IP / 2 Megapixel / Audio Bidireccional 5 m (16.4 ft) / Sirena 110 dB / Estrobo Rojo-Azul / IR 10 m (32.8 ft) / Doble Puerto 10/100 Mbps

SKU: DS-PEA22-B(B) Marca: HIKVISION Categoría: Estaciones Manuales de Emergencia

Garantía: 5 años

$8,756.63

Precios con IVA incluido

DESCRIPCIÓN

Estación de alarma de pánico IP con cámara integrada de 2 megapíxeles (1920 × 1080), diseñada para entornos que requieren respuesta inmediata ante emergencias. Incorpora alarma de un solo toque con protección antimanipulación, sirena de 110 dB con sonido configurable y estrobo dual de luz roja y azul para alerta visual y sonora simultánea. Ofrece audio bidireccional funcional hasta 5 metros (16.4 pies), compresión H.264/H.265 para transmisión eficiente, almacenamiento local en microSD/SDHC/SDXC hasta 128 GB, y conectividad dual mediante dos puertos de red 10/100 Mbps con soporte para protocolos RTSP, SNMP, SIP y ONVIF. Compatible con eHome para transmisión a redes públicas e integración con sistemas de gestión centralizada.

Características Generales
Cámara de 2 MP, resolución 1920 × 1080 Full HD
Compresión de video H.264 y H.265
Audio bidireccional hasta 5 m (16.4 ft)
Ranura microSD/SDHC/SDXC, máximo 128 GB
Sirena integrada de 110 dB, sonido configurable
Luz de alarma dual: rojo y azul con estrobo
Alarma de un toque con protección antimanipulación
Soporte eHome para transmisión a red pública
Dos puertos de red 10/100 Mbps
Protocolos: TCP/IP, RTSP, SNMP, SIP, ONVIF
Soporte RS-485
Compatible con Hik-Connect P2P (modo demo)
Requiere HikCentral para operación completa
Voltaje de operación: 100-240 VCA

Desempeño de Video y Audio
Resolución: 2 MP (1920 × 1080)
Compresión: H.264 / H.265
Audio bidireccional: hasta 5 m (16.4 ft)
Alcance IR: 10 m (32.8 ft)

Alarmas y Conectividad
Sirena: 110 dB, configurable
Estrobo dual: luz roja y azul
Alarma de un toque con antimanipulación
Puertos de red: 2 × 10/100 Mbps
Protocolos: TCP/IP, RTSP, SNMP, SIP, ONVIF
Interfaz: RS-485
eHome / Hik-Connect P2P (demo)

Físicas, Eléctricas y Almacenamiento
Diseño compacto tipo caja, instalación IP
Voltaje de operación: 100-240 VCA
Almacenamiento: microSD/SDHC/SDXC hasta 128 GB

ESPECIFICACIONES

Característica 1	**Alarma de pánico de un toque con antimanipulación integrada**
Característica 2	**Sirena configurable de 110 dB con estrobo dual rojo y azul**
Característica 3	**Audio bidireccional con cobertura hasta 5 m (16.4 ft)**
Característica 4	**Grabación local en microSD hasta 128 GB**
Característica 5	**Transmisión dual TCP/IP con soporte RTSP, SNMP, SIP y ONVIF**
Característica 6	**Compresión H.264/H.265 con eficiencia de ancho de banda optimizada**

MEMORIA TÉCNICA · DS-PEA22-B(B)

Número de parte de esta ficha: DS-PEA22-B(B). La información corresponde a esta variante.

DS-PEA22 Series
Box Panic Alarm Station
Key Features
- Supports network adaptive and video and audio adaptive to realize low latency
- H.264, H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, SNMP, HIK-SIP, RTSP
- Video collection and all-day monitoring with 2 MP HD IR camera
- Supports ISUP and Hik-Connect service for public network transmission
- Two-way audio function with up to 5 m communication distance
- Build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface
- Build-in loudspeaker and pickup with cracking voice prevention
- External audible and visual alarm
- Dual network ports
DS-PEA22 series box panic alarm station is designed with 2 MP HD camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio. It helps to realize immediate alarm and aid, which can be mainly applied to school, square, tourist

attraction, hospital, supermarket gate, market, station, parking lot,
etc.
- Model DS-PEA22 Series Box Panic Alarm Station
Build-in
camera
parameters
Camera 2 MP HD IR Camera, IR Distance ≥ 10 m
FOV Horizontal: 128°, Vertical: 75°, Diagonal: 147°
Day & night IR Cut Filter
Video compression
standard
H.264, H.264 SVC, H.265
Audio
paramete
rs
Audio input
1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
1-ch 3.5 mm Audio Interface for External Audio Input
Audio output
1-ch 3 W Build-in Loudspeaker
1-ch 3.5 mm Audio Interface for External Audio Output
Audio compression
standard
G.711 U/64Kbps, G.726 /16Kbps
Audio quality Noise Suppression and Echo Cancellation
Network
parameters
Network protocol TCP/IP, RTSP, SNMP, and HIK-SIP
Ethernet 10 M/100 M Self-adaptive Ethernet Port
Public network
transmission
ISUP 2.0/ Hik-Connect /Standard SIP
Network encryption Supports User Lock-in and Password Security Prompt
Alarm
One-touch alarm Supported
Tampering Alarm Supported
Device
interfaces
Ethernet port 2 RJ45 10 M/100 M Self-adaptive Ethernet Port
IO Input 2
IO Output 2
Alarm lamp Supported, Light Can be Configured Separately
Siren Supported, Sound Can be Configured Separately
SD Card
Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card,
Max. 128G
PSTN 1-ch
General
Power supply 100-240 VAC
Power consumption ≤ 24W
Working temperature -40 °C to +60 °C (-40 °F to 140 °F)
Working humidity 10% to 90%
Installation Hold Hoop and Wall Mounting
Dimensions 516.5 mm × 327.7 mm × 125 mm (20.33" × 12.90" × 4.92")
- Specifications
Modelo incluido en esta ficha
DS-PEA22-B(B)