

AL600ULX Series

Power Supply/Chargers

Description

Altronix AL600ULX series power supply/chargers convert a 115VAC, 60Hz input into a single fused, four (4), eight (8) or sixteen (16) fuse or PTC protected outputs. Outputs are selectable for 12VDC or 24VDC with a total of 6A max.



AL600ULPD8

Key Features

- Available with 1, 4, 8 or 16 outputs.
- Fused or PTC protected outputs.
- Supervision:
 - AC Fail.
 - Battery Fail and Battery Presence.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- Short circuit and overload protection.
- AC input and DC output options.
- UL Listed in the U.S. and Canada.
- CSFM and MEA Approved.
- Lifetime Warranty / Made in the U.S.A.
- All units are available in grey or red enclosure.

AL600ULX Series Power Supply Configuration Reference Chart

Altronix Model Number	Total Output Rating (A)	Input Rating: 115VAC, 60Hz	Input Fuse Rating	Power Distribution Module	Class 2 Rated Power-Limited Outputs (auto-resettable)	Number of Outputs	Fused Output Ratings	PTC Output Ratings	Accommodates Batteries
AL600ULX	6A	3.5A	5A/250V	N/A	—	1	6A	—	Two (2) 7AH
AL600ULXX									Two (2) 12AH
AL600ULPD4				PD4UL	—	4	3.5A	—	Two (2) 7AH
AL600ULPD4CB				PD4ULCB	✓	4	—	2.5A	Two (2) 7AH
AL600ULPD8				PD8UL	—	8	3.5A	—	Two (2) 7AH
AL600ULPD8CB				PD8ULCB	✓	8	—	2.5A	Two (2) 7AH
AL600ULXPD16				Two (2) PD8UL	—	16	3.5A	—	Two (2) 12AH
AL600ULXPD16CB				Two (2) PD8ULCB	✓	16	—	2.5A	Two (2) 12AH

AL600ULX Series

Power Supply/Chargers



Specifications

Input

Voltage 115VAC, 60Hz, 3.5A max.
Fusing 5A / 250V.

Outputs

Voltage 12VDC or 24VDC selectable.
Current 6A @ 12VDC or 24VDC continuous max.
Protection Fused 3.5A / PTC 2.5A.
Other Overvoltage protection.
Filtered and regulated.

Back-up Battery *(not included)*

Capacity 7AH / 12VDC (1 or 2 within enclosure).
12AH / 12VDC (requires larger "X" enclosure).
40 AH / 65 AH (requires separate enclosure).

Type Sealed lead acid or gel type.
Failover Upon AC loss, instantaneous.

Supervision

AC Failure Form "C" contacts.
Battery Form "C" contacts.

Indicators (LED)

Input 115VAC is present.
DC Output Powered.
Battery Discharged or not connected.

Agency Listings

Access Control UL294
Burglar Alarm UL603
Hospital Signaling UL1069
Fire Alarm UL1481
California State Fire Marshall Approved

Physical and Environmental

Dimensions (H x W x D)

AL600ULX, AL600ULPD4(CB), AL600ULPD8(CB):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm).
AL600ULXX, AL600ULXPD16(CB):
15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm).

Product / Shipping Weight (approx.)

Model	Product Weight	Shipping Weight
AL600ULX	7.6 lbs. (3.45 kg)	8.5 lbs. (3.86 kg)
AL600ULXX	9.3 lbs. (4.22 kg)	10.6 lbs. (4.81 kg)
AL600ULPD4(CB)	8.45 lbs. (3.83 kg)	9.35 lbs (4.24 kg)
AL600ULPD8(CB)	8.7 lbs. (3.95 kg)	9.6 lbs (4.35 kg)
AL600ULXPD16(CB)	11.4 lbs. (5.17 kg)	12.7 lbs. (5.76 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.):

12VDC: 37 BTU/Hr.

24VDC: 74 BTU/Hr.