

Router Inalámbrico / 3 Puertos 10/100 Mbps / Wi-Fi 2.4 GHz 802.11n / Antena 360° 1.5 dBi / CPU 650 MHz / RouterOS

SKU: RB931-2ND Marca: MIKROTIK Categoría: Routers Inalámbricos

Garantía: 3 años

$845.35

Precios con IVA incluido

DESCRIPCIÓN

El hAP mini es un punto de acceso inalámbrico compacto de 2.4 GHz diseñado para hogares y pequeñas oficinas. Integra tres puertos Ethernet 10/100 Mbps configurables —por defecto un puerto de Internet y dos LAN— que pueden reasignarse mediante las opciones de RouterOS. Su CPU de 650 MHz permite aprovechar las funciones avanzadas del sistema operativo, mientras que la antena omnidireccional de 360° y 1.5 dBi ofrece cobertura estable con potencia de salida de hasta 158 mW. El equipo sale configurado de fábrica como punto de acceso; basta con acceder a la página web de configuración y establecer una contraseña. Su consumo máximo de 3.5 W lo hace adecuado para operación continua.

Características Generales
3 puertos Ethernet 10/100 Mbps configurables
Wi-Fi 2.4 GHz 802.11 b/g/n
Antena omnidireccional 360° de 1.5 dBi
Potencia de salida de hasta 158 mW
CPU de 650 MHz con RouterOS
Consumo energético máximo de 3.5 W
Arquitectura RouterBOARD smips
No compatible con User Manager
Configuración inicial vía página web con contraseña
Preconfigurado como punto de acceso de fábrica

Desempeño
Wi-Fi 2.4 GHz 802.11 b/g/n
Antena omnidireccional 360°, 1.5 dBi
Potencia de salida hasta 158 mW
CPU de 650 MHz
3 puertos Ethernet 10/100 Mbps

Alimentación y Consumo
Consumo máximo: 3.5 W
Operación continua eficiente

Software y Arquitectura
Sistema operativo RouterOS
Arquitectura RouterBOARD smips
No compatible con User Manager
Configuración web con contraseña
Preconfigurado como punto de acceso

MEMORIA TÉCNICA · RB931-2ND

Número de parte de esta ficha: RB931-2ND. La información corresponde a esta variante.

1
hAP mini
The hAP mini is a small 2 GHz wireless access point for home or small offices. It has three ports, which are configured as one Internet port and two LAN ports, but can be reconfigured as desired, using the powerful RouterOS configuration options.
The unit is powered by microUSB and measures only 8 cm tall. Even with it's small size, the hAP mini is still quite powerful, as it uses the QCA9533 CPU, just like the bigger units in the widely successful hAP series.
- The device has an omnidirecional antenna built-in, and does not have a strict limiation on number of connected clients. It works in 2 GHz and supports 802.11b/g/n standards.
The powerful 650 MHz CPU gives you full access to the wide variety of features provided by the versatile RouterOS operating system, but if all you want is a simple access point - it is already configured out of the box. You simply need to open it's web configuration page and set a password for it.
hAP mini
hAP mini
- 2
hAP mini
hAP mini
Product code RB931-2nD
CPU QCA9533
CPU nominal frequency 650 MHz
CPU core count 1
Size of RAM 32 MB
10/100 Ethernet ports 3
Wireless
Built-in 2.4 GHz 802.11b/g/n, dual-chain
Wireless regulations
Specific frequency range may be limited by country regulations

Antenna gain 1.5 dBi
Antenna beam width 360°
Wireless chip model QCA9533
Supported input voltage 5 V (Jack)
Dimensions 48 x 78 x 81mm
License level 4
Operating System RouterOS
Max Power consumption 3.5 W
IncludedSpecifications
Wireless specifications
5 V 0.7 A
power adapter
RATE Tx (dBm) Rx (dBm)
1MBit/s 22 -96
11MBit/s 22 -89
6MBit/s 20 -93
54MBit/s 18 -74
MCS0 20 -93
MCS7 16 -71