

Kit de Conectores para Megafonía / 25 Vrms / Línea Equilibrada / Sin Fuente Externa / UL cUL CSFM

SKU: AM25CK Marca: FEDERAL SIGNAL INDUSTRIAL Categoría: Bocinas de Alerta y Notificación Masiva

Garantía: 3 años

$3,146.96

Precios con IVA incluido

DESCRIPCIÓN

El kit de interfaz AM25CK permite integrar altavoces amplificados SelecTone® en sistemas de megafonía existentes que operan a 25 Vrms. El dispositivo acondiciona la señal de audio entrante al nivel requerido por el amplificador interno del altavoz, generando una línea equilibrada SelecTone®. Su conexión directa al borde de tarjeta del altavoz elimina la necesidad de cableado adicional complejo. La operación pasiva no requiere fuente de alimentación externa, facilitando su instalación en entornos profesionales. La unidad está aprobada por CSFM, UL y cUL para cumplir con estándares de seguridad en instalaciones críticas.

Características Generales
Integración con sistemas de megafonía de 25 Vrms
Acondicionamiento de señal de audio para nivel de amplificador interno
Generación de línea equilibrada SelecTone®
Conexión directa a conector de borde de tarjeta
Operación pasiva sin alimentación externa
Aprobaciones CSFM, UL y cUL

Desempeño
Tipo de sistema: Megafonía de 25 Vrms
Función principal: Interfaz para altavoces amplificados SelecTone®
Línea de audio: Línea equilibrada SelecTone®
Acondicionamiento: Señal convertida al nivel de entrada del amplificador interno

Físicas y Eléctricas
Conexión: Directa a conector de borde de tarjeta
Alimentación: No requiere alimentación externa
Operación: Pasiva
Compatibilidad: Altavoces amplificados SelecTone®

Certificaciones
CSFM: Aprobado
UL: Aprobado
cUL: Aprobado
Aplicación: Instalaciones de megafonía profesional

ESPECIFICACIONES

Característica 1	**Amplía infraestructura de megafonía sin sustituir equipos existentes**
Característica 2	**Acondiciona señal de audio para amplificador interno del altavoz**
Característica 3	**Conexión directa a borde de tarjeta que reduce tiempo de instalación**
Característica 4	**Funcionamiento pasivo que elimina puntos de fallo externos**
Característica 5	**Aprobado por CSFM UL y cUL para uso profesional**
Característica 6	**Minimiza ruido y distorsión mediante línea de audio equilibrada**

MEMORIA TÉCNICA · AM25CK

Número de parte de esta ficha: AM25CK. La información corresponde a esta variante.

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
- OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM
LISTING SERVICE
- LISTING No. 7135-0811:0003 Page 1 of 1
CATEGORY: 7135 -- AUDIBLE DEVICES
LISTEE: Federal Signal, 2645 Federal Signal Drive, University Park, IL 60466-3195
Contact: Sean Moloney (708) 587-3324 Fax (708) 534-4878
DESIGN: Models 50GC, *54GC, *ASLP, 50GCB, *54GCB, AM300GCX, AM300X, 300GC, *304GC, *ASHP, 302GC, *314GC, *ASUP, 300GCX, *304GCX, *ASHH, 302GCX, *314GCX, *ASUH, 300X, 302X, *304X, *ASHX, *314X, *ASUX, *WA410X, and *WA412X audible devices. Suitable for indoor or outdoor use. May include the following optional devices: Models 300CKS, AM25CK, *CK25, AM70CK, and *CK70 connector cards; Models TC-WL, TC-YP, TC-HL, TC-BL, TC-YW, TC-HN, TC-BP, TC-ST, TC-SW, TC-TW, TM1 through TM9, TM11, UTM, and *UTC tone cards. Refer to listee's data sheet for detailed product description and operational considerations. Additional information may also be located in UL Hazardous Locations Equipment Directory and UL Fire Protection Equipment Directory.
RATING:
INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.
MARKING: Listee's name, model number, electrical rating, and UL label.
APPROVAL: Listed as audible devices for use with separately listed compatible fire alarm control units. Models AM300GCX, 300GCX, 302GCX, *304GCX, *ASHH, *314GCX, and *ASUH are suitable for use in the following hazardous locations: Class I, Groups A, B, C and D, Division 2; *Class II, Groups F and G, Division 2 and Class III. Models AM300X, 300X, 302X, *304X, *ASHX, *314X, and *ASUX are suitable for use in hazardous locations: Class I, Groups B, C and D. Models *WA410X, and *WA412X are suitable for use in hazardous locations, Class I, Groups C and D, Type 4X. Refer to manufacturer's Installation Manual for details.
NOTE: If the distinctive three-pulse Temporal Pattern Fire Alarm Evacuation signal (for total evacuation) in accordance with NFPA 72, 2002 Edition is required, the appliance must be used with a fire alarm control unit that can generate the temporal pattern signal.
*Rev. 02-03-04
July 01, 2010

FRANCIS MATEO, Program Coordinator
Date Issued: Listing ExpiresJune 30, 2011
Authorized By:
Fire Engineering Division
This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee 's data sheet, installation instructions and/or other suitable information sources.