

Kit de Tornillos de Fijación / 4 Piezas / Compatibilidad 2 y 3 Polos / Interruptores Termomagnéticos QR

SKU: MSQR3 Marca: SIEMENS Categoría: Centros de Carga, Interruptores y Protección

Garantía: 3 años

$217.85

Precios con IVA incluido

DESCRIPCIÓN

El kit de tornillos de fijación está diseñado para asegurar la instalación de interruptores termomagnéticos de la serie QR en aplicaciones de distribución eléctrica. Incluye cuatro piezas que garantizan el anclaje firme de los dispositivos en sus bases o rieles de montaje. Es compatible con modelos de 2 y 3 polos, ofreciendo versatilidad para distintas configuraciones de protección de circuitos. Este set es esencial para proyectos de instalación nueva, expansión o reposición de componentes en tableros eléctricos industriales y comerciales.

Kit de fijación para interruptores termomagnéticos de la serie QR.
Contenido: 4 tornillos para montaje y anclaje de dispositivos.
Compatibilidad garantizada con interruptores de 2 y 3 polos.
Aplicación en tableros de distribución eléctrica industrial y comercial.
Uso recomendado para instalación nueva, expansión o mantenimiento.

Desempeño
Aplicación: Fijación de interruptores termomagnéticos QR
Compatibilidad: Dispositivos de 2 y 3 polos
Uso recomendado: Tableros de distribución eléctrica

Físicas / Eléctricas
Cantidad: 4 tornillos de fijación
Tipo: Anclaje mecánico para montaje en base
Diseño: Específico para serie QR

Contenido del Paquete
4 tornillos para fijación de interruptores termomagnéticos QR

ESPECIFICACIONES

Característica 1	**Set completo para fijación de 4 interruptores QR**
Característica 2	**Compatible con dispositivos termomagnéticos de 2 y 3 polos**
Característica 3	**Montaje estable y seguro en paneles de distribución**
Característica 4	**Repuesto indispensable para mantenimiento de tableros eléctricos**
Característica 5	**Diseño específico para la serie de interruptores QR**
Característica 6	**Simplifica instalación de componentes de protección eléctrica**

MEMORIA TÉCNICA · MSQR3

Número de parte de esta ficha: MSQR3. La información corresponde a esta variante.

Siemens Industry, Inc. SPEEDFAX™ Product Catalog 7-387
MOLDED CASE
CIRCUIT BREAKERS
Siemens / Speedfax Previous folio: 6-28 Updated by TA 02/03/11
Molded Case Circuit Breakers
QR 250A Frame Selection/Dimensions
n Built to order. Allow 2–3 weeks for delivery. Note: QR breakers are UL Listed for reverse feed applications.
a HACR rated.
Enclosures Section 6
For external accessories, please refer to pages
- 7-169 to 7-174
Continuous Current Rating @ 40°C
2-Pole 240V AC Catalog Number
3-Pole 240V AC Catalog Number
Type QR2
a
100 QR22B100 QR23B100
125 QR22B125 QR23B125
150 QR22B150 QR23B150
175 QR22B175 QR23B175
200 QR22B200 QR23B200
225 QR22B225 QR23B225
250 QR22B250 QR23B250
Type QRH2
a
100 QRH22B100 n QRH23B100
125 QRH22B125 QRH23B125
150 QRH22B150 QRH23B150
175 QRH22B175
n QRH23B175
200 QRH22B200 QRH23B200
225 QRH22B225 QRH23B225
250 QRH22B250 QRH23B250
Type HQR2
a
100 HQR22B100 n HQR23B100
125 HQR22B125 HQR23B125
150 HQR22B150 HQR23B150
175 HQR22B175
n HQR23B175
200 HQR22B200 HQR23B200

225 HQR22B225 HQR23B225
250 HQR22B250 HQR23B250
Type HQR2H
a
100 HQR22B100H HQR23B100H
125 HQR22B125H HQR23B125H
150 HQR22B150H HQR23B150H
175 HQR22B175H HQR23B175H
200 HQR22B200H HQR23B200H
225 HQR22B225H HQR23B225H
250 HQR22B250H HQR23B250H
UL 489 Interrupting Ratings
Breaker Type
RMS Symmetrical Amperes (kA) Volts AC (50/60 Hz)
240
QR2 10
QRH2 25
HQR2 65
HQR2H 100
Lugs For 75°C Wire
Catalog
Number
Lug
Body
Lug
Wire Range
3TA1QR300 Al
#3 - 300 Kcmil Al/Cu
3TC1QR250 Cu
#3 - 300 Kcmil Cu ONLY
CCQ250 CMP
#6 AWG - 350kcmil Al/Cu
Enclosures (Neutral Included)
Type
Catalog Number
1 QR2N1S or QR2N1F
3R QR2N3R3
12 QR2N12
4X QR2N4X
4X316 QR2N4X316
Shipping Weights
Number of Poles
Number per Carton
Shipping Weight (lbs.)
2 1 3.2
3 1 4.5
Ordering Information
Load side 3TA1QR300 lugs are mounted and included when circuit breaker is ordered. For line and load lugs (3TA1QR300) installed at no additional charge, add suffix “L” to catalog number.
50° C Calibration - See page 7-165.
400HZ. - See page 7-165.
2.53’’
7’’
D
3’’
2-pole
4.5’’ 3-pole
Product Category MCCB
Revised on 05/31/24
- Siemens Industry, Inc. SPEEDFAX™ Product Catalog 7-397
MOLDED CASE
CIRCUIT BREAKERS
Molded Case Circuit Breakers
QR Accessories Selection
Shunt Trip
Control Voltage
In Rush
Shunt Trip
Shunt Trip and Auxiliary
Switch Combination
AC DC Catalog Number Catalog Number
— 24 1.1A S07QR2 S07QR2A
120 - 240 48 2.0A AC / 1.8A DCS01QR2 S01QR2A
Auxiliary Switch
Contains (1) or (2) sets of “A” contacts and “B” contacts
Maximum Control Supply Voltage (V)
Maximum Allowable Current (A)
Single Auxiliary 1A -1B Contact Catalog Number
Double Auxiliary 2A - 2B Contact Catalog Number
250 AC /125 DC 5 AC / 0.5 DC A01QR2 A02QR2
External Accessories
Description Catalog Number
Padlock Device HPLQR
Mounting Screw Kit MSQR3
Handle Blocking Device HBLQR
Handle Sliding-bar Interlock SBMIQR
Padlock Device HPLQR Handle Block Device HBLQR Mechanical Interlock SBMIQRPadlock Device HPLQR Handle Block Device HBLQR Mechanical Interlock SBMIQRPadlock Device HPLQR Handle Block Device HBLQR Mechanical Interlock SBMIQR
Revised on 04/10/17