

MODELO		Solo Frío		Frío - Calor			
Código de Unidad		QCI-R32-12K-110	QCI-R32-12K-220	QHI-R32-12K-110	QHI-R32-12K-220	QHI-R32-24K-220	QHI-R32-36K-220
Capacidad Nominal	Enfriamiento (W)	3500	3520	3500	3520	7040	10000
	Calefacción (W)	-	-	3600	3600	7040	10000
Deshumidificación	Kg/h	1.0	1.0	1.0	1.0	2.48	3.6
Consumo de Potencia Nominal	Enfriamiento (W)	1,115	1,115	1,115	1,200	2,400	3,300
	Calefacción (W)	-	-	1,100	1,000	-	2,900
Corriente de Operación Nominal	Enfriamiento (A)	11.8	5.6	10.5	5.5	12	15
	Calefacción (A)	-	-	9.0	4.7	-	13
Potencia / Corriente Máx. Entrada	W / A	1400 / 12	1750 / 8.5	1400 / 12	1850 / 8	3400 / 16	3700 / 17
Parámetro de Placa	SEER (W/W)	SEER 19	SEER 19	SEER 19	SEER 18	SEER 18	SEER 18
	SCOP (W/W)	-	-	3.60	3.60	3.27	3.45
Alimentación Eléctrica	V / Ph / Hz	115V / 1 / 60Hz	208-230V / 1 / 60Hz	115V / 1 / 60Hz	208-230V / 1 / 60Hz	208-230V / 1 / 60Hz	208-230V / 1 / 60Hz
Refrigerante / Carga	Tipo / g	R32 / 400g	R32 / 400g	R32 / 620g	R32 / 540g	R32 / 1300g	R32 / 2000g
Presión Máxima	Desc. / Suc. (MPa)	4.3 / 2.5	4.3 / 2.5	4.3 / 2.5	4.3 / 2.5	4.3 / 2.5	4.3 / 2.5
Caudal de Aire / Nivel de Ruido	m³/h / dB(A)	550 / 42	600 / 42	620 / 41	600 / 41	1300 / 50	1600 / 52
Peso Neto (Int. / Ext.)	Kg	8 / 20	7.5 / 20.5	8 / 21.5	7.5 / 22	13 / 33	16.0 / 44.5
UNIDAD INTERIOR							
Dimensiones Netas (A x Prof x A)	mm	761×295×200	761×295×200	761×295×200	761×295×200	1089×328×227	1250×358×253
Dimensiones de Empaque	mm	825×367×277	825×367×277	825×367×277	825×367×277	1155×397×312	1340×445×355
Conexión Válvulas	Líqu. / Gas	DG4 / DG8	DG4 / DG8	DG4 / DG8	DG4 / DG8	DG4 / DG13	DG4 / DG13
UNIDAD EXTERIOR Y COMPRESOR							
Parámetros del Compresor	Modelo	HIGHLY GSX098CKNA6JG8	GMCC KSNB9D2BUE4A31	HIGHLY GSX098CKNA6JG8	GMCC KSN89D2BUE4A31	GMCC KTN150D43UFZC31	GMCC KTM240D43UKUA2
Entrada Compresor / Parámetro	W	3510 / 794	2770 / 715	3510 / 794	2770 / 715	4570 / 1210	8780 / 3635
Dimensiones Netas (A x Prof x A)	mm	711×280×538	711×280×538	711×280×538	711×280×538	824×320×655	890×355×700
Dimensiones del Empaque	mm	825×345×595	825×345×595	825×345×595	825×345×595	945×400×715	1015×425×762