



Switch Industrial PoE+ hasta 180 watts , Ideal para temperaturas Extremas y protección contra descargas, 1 puerto PoE++ 60W y 3 puertos PoE+ 30W, 2 SFP Uplink

SKU: RG-NIS2100-4GT2SFP-HP

Marca: RUJIE

Categoría: Industrial

\$2,929.36

Precios con IVA incluido

DESCRIPCIÓN

<div style='width: 100%; max-width: 1200px; margin: 0 auto; font-family: sans-serif; line-height: 1.6; color: inherit; background-color: transparent;*><div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;*><div style='flex: 1 1 300px; min-width: 280px;*><h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;*>Key Specification</h3><ul style='padding-left: 20px; font-size: 15px; color: inherit;*><li style='margin-bottom: 5px;*>Number of 1 Gbps SFP Ports: 2<li style='margin-bottom: 5px;*>Number of 10/100/1000BASE-T Ports: 4<li style='margin-bottom: 5px;*>Layer: 2<li style='margin-bottom: 5px;*>Switching Capacity: 12 Gbps<li style='margin-bottom: 5px;*>Forwarding Rate: 8.9 Mpps<li style='margin-bottom: 5px;*>MAC Address Table Size: 8000<li style='margin-bottom: 5px;*>Max. Number of VLANs: 16<li style='margin-bottom: 5px;*>Dimensions (W x D x H): 50 mm x 155 mm x 130 mm (1.97 in. x 6.10 in. x 5.12 in.)<li style='margin-bottom: 5px;*>Net Weight: 0.77 kg (1.70 lbs)<li style='margin-bottom: 5px;*>Mean Time Between Failure (MTBF): > 200,000 hours<li style='margin-bottom: 5px;*>Warranty: 5 years<li style='margin-bottom: 5px;*>Port Surge Protection: Common mode: 6 kV<li style='margin-bottom: 5px;*>Certification: CE</div><hr style='border: 0; border-top: 1px solid rgba(150, 150, 150, 0.3); margin: 30px 0;*><div style='display: flex; flex-wrap: wrap; gap: 20px; justify-content: center; margin-top: 30px;*><div style='flex: 1 1 300px; min-width: 280px;*> src='https://ftp3..mx/usuarios/fotos/RGNIS21004GT2SFPHP/229644-rgnis01.png' alt='*> class='fr-fic fr-dii'></div><div style='flex: 1 1 300px; min-width: 280px;*> src='https://ftp3..mx/usuarios/fotos/RGNIS21004GT2SFPHP/229644-rgnis02.png' alt='*> class='fr-fic fr-dii'></div><div style='flex: 1 1 300px; min-width: 280px;*> src='https://ftp3..mx/usuarios/fotos/RGNIS21004GT2SFPHP/229644-rgnis03.png' alt='*> class='fr-fic fr-dii'></div></div><p>
</p><p style='text-align: center;*> data-pasted='true'>>Especificaciones de Energía</p><p>>Switch DC input: </p><p>>● Rated voltage range: 46 V DC to 57 V DC </p><p>>● Rated current range: 4.2 A </p><p>>● Consumo MIN. 12 W (sin carga PoE) </p><p>>● Consumo MAX. 192 W (con carga PoE) </p><p>
</p><p>>Fuente RG-NIS-PA240-54 (AC input): </p><p>>● Rated input voltage: 100 V AC to 240 V AC, 50/60 Hz </p><p>>● Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz </p><p>>● Rated input current: 3.5 A Output </p><p>>● Rated output voltage: 54 V DC </p><p>>● Maximum output current: 4.4 A </p><p>
</p><p>>Fuente RG-NIS-PA120-54 (AC input): </p><p>>● Rated input voltage: 100 V AC to 240 V AC, 50/60 Hz </p><p>>● Maximum input voltage: 85 V AC to 264 V AC, 47 Hz to 63 Hz </p><p>>● Rated input current: 1.5 A Output </p><p>>● Rated output voltage: 54 V DC </p><p>>● Maximum output current: 2.5 A</p></div>

ESPECIFICACIONES

Característica 1	Operación confiable en temperaturas extremas de -40°C a 75°C
Característica 2	Alimentación PoE++ 60W para dispositivos de alto consumo como PTZ o paneles Wi-Fi
Característica 3	Protección contra sobretensiones de 6 kV en modo común para instalaciones eléctricamente ruidosas
Característica 4	Doble enlace SFP de fibra óptica para extensión de red sin degradación
Característica 5	Capacidad de conmutación de 12 Gbps con reenvío de 8.9 Mpps sin bloqueo
Característica 6	Diseño compacto de 50 x 155 x 130 mm para gabinetes de espacio reducido

Documento generado por RimeCommerce - SOITMEX | 03/08/2026 07:52