



Switch PoE+ Empresarial 125 Watts, Administrable L2+, 8 Puertos PoE Gigabit , 2 Puertos Uplink Gigabit y 2 Puertos Uplink SFP 2.5G

SKU: RG-S2915-10GT2MS-P-L Marca: RUIJIE Categoría: Switches PoE

\$6,497.10

Precios con IVA incluido

DESCRIPCIÓN

<div style='width: 100%; max-width: 1200px; margin: 0 auto; font-family: sans-serif; line-height: 1.6; color: inherit; background-color: transparent;*> <div style='display: flex; flex-wrap: wrap; gap: 30px; margin-bottom: 30px;*> <div style='flex: 1 1 300px; min-width: 280px;*> <h3 style='font-size: 22px; border-bottom: 2px solid currentColor; padding-bottom: 5px; margin-top: 0; color: inherit; opacity: 0.8;*>Key Specification</h3> <ul style='padding-left: 20px; font-size: 15px; color: inherit;*> <li style='margin-bottom: 5px;*>Fixed Service Ports: 10 x 10/100/1000BASE-T ports, ports 1 to 8 supporting PoE/PoE+
2 x 1GE/2.5GE SFP ports <li style='margin-bottom: 5px;*>Management port: 1 x RJ45 console port <li style='margin-bottom: 5px;*>Switching capacity: 30 Gbps <li style='margin-bottom: 5px;*>Forwarding rate: 22.5 Mpps <li style='margin-bottom: 5px;*>Capacity of MAC address table: 16000 <li style='margin-bottom: 5px;*>Power module: 1 x fixed power module <li style='margin-bottom: 5px;*>Fan module: 1 x fan module <li style='margin-bottom: 5px;*>Cooling mode: Fan cooling <li style='margin-bottom: 5px;*>Input power: Rated input voltage range: 100V AC to 240V AC, 50/60Hz
Max. input voltage range: 90V AC to 264V AC, 50/60Hz <li style='margin-bottom: 5px;*>Power consumption: 141W (PoE budget: 125W) <li style='margin-bottom: 5px;*>Surge protection: 10 kV <li style='margin-bottom: 5px;*>Dimensions (W x D x H): 297 mm x 170 mm x 44.5 mm (11.69 in. x 6.69 in. x 1.75 in.) <li style='margin-bottom: 5px;*>Temperature: Operating temperature: 0°C to 45°C (32°F to 113°F)
Storage temperature: -40°C to +70°C (-40°F to +158°F) <li style='margin-bottom: 5px;*>Warranty: 3 years </div> <div style='display: flex; flex-wrap: wrap; gap: 20px; margin-bottom: 30px;*> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Ports</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>Fixed Service Ports: 10 x 10/100/1000BASE-T ports, ports 1 to 8 supporting PoE/PoE+ <li style='margin-bottom: 5px;*>Uplink Ports: 2 x 1GE/2.5GE SFP ports </div> </div> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Performance</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>Switching capacity: 30 Gbps <li style='margin-bottom: 5px;*>Forwarding rate: 22.5 Mpps <li style='margin-bottom: 5px;*>MAC address table: 16000 entries </div> </div> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Power</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>Input power: 100V AC to 240V AC, 50/60Hz <li style='margin-bottom: 5px;*>Max. input voltage range: 90V AC to 264V AC, 50/60Hz <li style='margin-bottom: 5px;*>Power consumption: 141W (PoE budget: 125W) <li style='margin-bottom: 5px;*>Power module: 1 x fixed </div> </div> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Physical</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>Cooling: Fan cooling <li style='margin-bottom: 5px;*>Fan module: 1 x fan module <li style='margin-bottom: 5px;*>Surge protection: 10 kV <li style='margin-bottom: 5px;*>Dimensions: 297 mm x 170 mm x 44.5 mm (11.69 in. x 6.69 in. x 1.75 in.) </div> </div> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Environmental</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>Operating temperature: 0°C to 45°C (32°F to 113°F) <li style='margin-bottom: 5px;*>Storage temperature: -40°C to +70°C (-40°F to +158°F) </div> </div> <div style='flex: 1 1 250px; border: 1px solid rgba(150, 150, 150, 0.4); border-radius: 8px; overflow: hidden; display: flex; flex-direction: column;*> <div style='padding: 15px; border-bottom: 1px solid rgba(150, 150, 150, 0.2); font-weight: bold; font-size: 18px; color: inherit;*>Warranty</div> <div style='padding: 15px; color: inherit;*> <ul style='padding-left: 20px; margin: 0; font-size: 14px; list-style-type: disc;*> <li style='margin-bottom: 5px;*>>3 years </div> </div> <div style='display: flex; flex-wrap: wrap; gap: 20px; margin-bottom: 30px;*> <div style='flex: 1 1 100%; min-width: 280px;*> src='https://ftp3..mx/usuarios/fotos/RGS291510GT2MSPL/217851-02.png' alt=''> </div> <div style='flex: 1 1 100%; min-width: 280px;*> src='https://ftp3..mx/usuarios/fotos/RGS291510GT2MSPL/217851-01.png' alt=''> </div> </div> <hr style='border: 0; border-top: 1px solid rgba(150, 150, 150, 0.3); margin: 30px 0;*> </div>

ESPECIFICACIONES

Característica 1	Presupuesto PoE+ de 125W para dispositivos de alto consumo
Característica 2	Capacidad de conmutación de 30Gbps sin bloqueo
Característica 3	Protección contra sobretensiones de 10kV en puertos
Característica 4	Tabla MAC de 16,000 direcciones para redes extensas
Característica 5	Ventilación activa con módulo de fan redundante
Característica 6	Diseño compacto 1U para instalación en rack estándar